






No	Description	Note	Date	Rev
1	First release	Charles	2021.11.25	A1




ES8-M(B)





ES8-M(O/R)





ES8-M(B/O/R)-M6-(0/1/2)





ES8-M(B/O/R)-35/50/70-(0/1/2)





ES8-M(B/O/R)-T-(0/1/2)



ES8-M(B/O/R)-B-(0/1/2)



ES8 MALE CONNECTOR



ES8 FEMALE 90° SHAPE CONNECTOR

ES8-M(B/O/R)-(B/T/M6/35/50/70)-(0/1/2)

- B:BLACK
- O:ORANGE
- R:RED
- B:Busbar
- T:Threaded
- M6:M6x1.0
- 35:35mm²crimp
- 50:50mm²crimp
- 70:70mm²crimp
- 0: Blank No Keyway
- 1: 30°
- 2: 45°

ES8-F(I / L)-(B/O/R)-(35/50/70)-(0/1/2)

- I: 180° SHAPE
- L: 90° SHAPE
- B:BLACK
- O:ORANGE
- R:Red
- 35:35mm²crimp
- 50:50mm²crimp
- 70:70mm²crimp
- 0: Blank No Keyway
- 1: 30°
- 2: 45°

NOTE:
 1.Specification subject to change without notice.
 2.Tolerance ± 1mm
 3.Proper Installation and fixation are required to prevent stress due to cable bending or hanging which will cause quality and electrical hazard Issue.
 4.Operation temperature:-40℃~+125℃

LEADER TECHNOLOGY
 TECHNICAL CENTER APPROVED
 TECHNICAL SUPPORT
 INFO@LEADERGROUP-CN.COM
 WWW.LEADERGROUP-CN.COM



DRAWN: CHARLES	PART NO. LD0408
CHECKED Brandon	TITLE: ES8 Series
APPROVED Mike	
SHEET 1/1	UNIT mm
	SCALE * A4
	SIZE A4
	REV A1